



Telephone: 01406 540777
Email: info@skycraft.ltd
Website: www.skycraft.ltd

Riverside House
Bloodfold Farm
Ravens Bank
Saturday Bridge
Holbeach
Lincolnshire
PE12 8SR

MATERIAL SAFETY DATA SHEET

Reference : D920
REVISION : 1
REVISION DATE : 21/12/04
Printed Date : 21/12/04
Page Number : 1 of 3

1. IDENTIFICATION OF PREPARATION

D920 Flexible White P/U Primer

APPLICATION Primer for treated steel, aluminium and nitrate/butyrate doped structures

COMPANY/UNDERTAKING IDENTIFICATION Skycraft Ltd Telephone: 01406 540777
Riverside House
Bloodfold Farm
Ravens Bank
Saturday Bridge
Holbeach
Lincs PE12 8SR U.K.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	EC No	CAS-NO	Content	Classification
2- Methoxy-1-Methylethyl Acetate	203-603-9	108-65-6	1-5%	R10 Xi;R36
Butyl Acetate - norm	204-658-1	123-86-4	1.5%	R10 R66 R67
Iso-Butanol	201-148-0	78-83-1	< 1%	R10 Xi;R37/38 R41 R67
Xylene	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

Harmful by inhalation and in contact with skin.
Classification Xn;R20/21

4. FIRST AID MEASURES

EYES Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with lots of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

SKIN Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

INHALATION Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention.

INGESTION NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Do not induce vomiting. Remove victim immediately from source of exposure, Get medical attention immediately. Provide rest, warmth and fresh air.

5. FIRE FIGHTING MEASURE

EXTINGUISHING MEDIA Use fire extinguishing media appropriate for surrounding materials. This product is not flammable.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS Wear necessary protective equipment Absorb in vermiculite, dry sand or earth and place in containers. Do not contaminate water sources or sewer.

7. STORAGE AND HANDLING

USAGE PRECAUTIONS Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS Store in tightly closed original container in a cool, dry, well ventilated place. Keep in original container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENT NAME	STD	LT-ppm	LT-mg/m3	ST-ppm	ST-mg/m3
Xylene	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm (Sk)	441 mg/m3(Sk)
Iso-Butanol	OES	50 ppm	154 mg/m3	75 ppm	231 mg/m3
Butyl acetate - norm	OES	150 ppm	724 mg/m3	200 ppm	966 mg/m3
2-methoxy-1-methylethyl acetate	OES	50 ppm (Sk)	274 mg/m3 (Sk)	100 ppm (Sk)	584 mg/m3 (Sk)

ENGINEERING MEASURES Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Limit.

HAND PROTECTION Use protective gloves.

EYE PROTECTION Wear approved safety goggles.

OTHER PROTECTION Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES DO NOT SMOKE IN WORK AREA. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin become contaminated. Use appropriate skin cream to prevent drying of the skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

10. STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions.

CONDITIONS TO AVOID Avoid contact with acids and oxidising substances

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of carbon dioxide (CO₂), carbon monoxide (CO)

11. TOXICOLOGICAL INFORMATION

INHALATION Harmful by inhalation. May cause irritation to the respiratory system.

INGESTION Harmful if swallowed.

SKIN CONTACT Harmful in contact with skin. Irritating to skin.

EYE CONTACT Irritating to eyes.

TARGET ORGANS Skin. Eyes. Respiratory system. Lungs.

Reference : D950
REVISION : 1
REVISION DATE : 21/12/04
Printed Date : 21/12/04
Page Number : 3 of 3

12. ECOLOGICAL INFORMATION

ECOTOXICITY Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified
SEA TRANSPORT NOTES	Not Classified
AIR TRANSPORT NOTES	Not Classified
UN NO. ROAD	1263

15. REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS Xylene

RISK PHRASES R20/21 Harmful by inhalation and in contact with skin

SAFETY PHRASES
S23 Do not breathe vapour/spray
S38 In case of insufficient ventilation, wear suitable respiratory equipment
S38/37 Wear suitable protective clothing and gloves
S60 This material and container must be disposed of as hazardous waste

STATUTORY INSTRUMENTS Chemicals (Hazard Information and Packaging) Regulations

APPROVED CODE OF PRACTICE Classification and Labelling of Substances and Preparations Dangerous for Supply

GUIDANCE NOTES

Occupational Exposure Limits EH40

16. OTHER INFORMATION

RISK PHRASES IN FULL	R10 Flammable
	R20/21 Harmful by inhalation and in contact with skin
	R36 Irritating to eyes
	R37/38 Irritating to respiratory system and skin
	R38 Irritating to skin
	R41 Risk of serious damage to eyes
	R66 Repeated exposure may cause skin dryness or cracking
	R67 Vapours may cause drowsiness and dizziness