



Telephone: 01406 540777
Email: info@skycraft.ltd
Website: www.skycraft.ltd

Riverside House
Bloodfold Farm
Ravens Bank
Saturday Bridge
Holbeach
Lincolnshire
PE12 8SR

MATERIAL SAFETY DATA SHEET

Reference : D950
REVISION : 1
REVISION DATE : 21/12/04
Printed Date : 21/12/04
Page Number : 1 of 3

1. IDENTIFICATION OF PREPARATION

D950 Flexible P/U Gloss

APPLICATION Finishing gloss for D920

COMPANY/UNDERTAKING IDENTIFICATION Skycraft Ltd Telephone: 01406 540777
Riverside House
Bloodfold Farm
Ravens Bank
Saturday Bridge
Holbeach
Lincs PE12 8SR U.K.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	EC No	CAS-NO	Content	Classification
2-Butoxyethanol	203-905-0	111-76-2	< 1%	Xn;R20/21/22 Xi;R36/38
2- Methoxy-1-Methylethyl Acetate	203-603-9	108-65-6	5-10%	R10 Xi;R36
Butyl Acetate - norm	204-658-1	123-86-4	5-10%	R10 R66 R67
Iso-Butanol	201-148-0	78-83-1	< 1%	R10 Xi;R37/38 R41 R67
Xylene	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

Flammable. Irritating to skin. Harmful by inhalation and in contact with skin.
Classification Xn;R20/21. Xi;R38. R10

4. FIRST AID MEASURES

EYES Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with lots of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

SKIN Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

INHALATION Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention.

INGESTION NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Do not induce vomiting. Remove victim immediately from source of exposure, Get medical attention immediately. Provide rest, warmth and fresh air.

GENERAL INFORMATION NOTE! Keep affected person away from heat, sparks and flames.

5. FIRE FIGHTING MEASURE

EXTINGUISHING MEDIA	Fire can be extinguished using Carbon dioxide (CO ₂). Dry chemicals, sand, dolomite etc.
SPECIFIC HAZARDS	Fire creates; Vapours/gases/fumes of carbon dioxide (CO ₂), carbon monoxide (CO)

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS	Wear necessary protective equipment Absorb in vermiculite, dry sand or earth and place in containers. Do not contaminate water sources or sewer.
-----------------------	--

7. STORAGE AND HANDLING

USAGE PRECAUTIONS	Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Static electricity and formation of sparks must be prevented.
STORAGE PRECAUTIONS	Store in tightly closed original container in a cool, dry, well ventilated place. Keep in original container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENT NAME	STD	LT-ppm	LT-mg/m3	ST-ppm	ST-mg/m3
Xylene	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm (Sk)	441 mg/m3(Sk)
Iso-Butanol	OES	50 ppm	154 mg/m3	75 ppm	231 mg/m3
2-Butoxethanol	OES	25 ppm (Sk)		50 ppm (Sk)	
Butyl acetate - norm	OES	150 ppm	724 mg/m3	200 ppm	966 mg/m3
2-methoxy-1-methylethyl acetate	OES	50 ppm (Sk)	274 mg/m3 (Sk)	100 ppm (Sk)	584 mg/m3 (Sk)

ENGINEERING MEASURES	Provide adequate general and local exhaust ventilation.
RESPIRATORY EQUIPMENT	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Limit.
HAND PROTECTION	Use protective gloves.
EYE PROTECTION	Wear approved safety goggles.
OTHER PROTECTION	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
HYGIENE MEASURES	DO NOT SMOKE IN WORK AREA. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin become contaminated. Use appropriate skin cream to prevent drying of the skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
------------	--------

10. STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid contact with acids and oxidising substances
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates: Toxic gases/vapours/fumes of carbon dioxide (CO ₂), carbon monoxide (CO)

11. TOXICOLOGICAL INFORMATION

INHALATION	Harmful by inhalation. May cause irritation to the respiratory system.
INGESTION	Harmful if swallowed.
SKIN CONTACT	Harmful in contact with skin. Irritating to skin.
EYE CONTACT	Irritating to eyes.
TARGET ORGANS	Skin. Eyes. Respiratory system. Lungs.

Reference : D950
REVISION : 1
REVISION DATE : 21/12/04
Printed Date : 21/12/04
Page Number : 3 of 3

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

UK ROAD CLASS	3	PAINT OR PAINT RELATED MATERIAL	
PROPER SHIPPING NAME	1263	UK ROAD PACK GR.	III
UN NO. ROAD	3	ADR CLASS	Class 3; Flammable liquids
ADR CLASS NO.	III	HAZARD NO. (ADR)	30
ADR PACK GROUP	3	HAZCHEM CODE	3Y
ADR LABEL NO.	30GF1-III.30GF1-sp	RID CLASS NO.	3
CEFIC TEC(R) NO.	III	UN NO. SEA	1263
RID PACK GROUP	3	IMDG PACK GR.	III
IMDG CLASS	3-05	MFAG	See Guide
EMS	No	UN NO. AIR	1263
MARINE POLLUTANT	3	AIR PACK GR.	III
ICAO CLASS			

15. REGULATORY INFORMATION

LABELLING



HARMFUL

CONTAINS	XYLENE
RISK PHRASES	R10 Flammable R38 Irritating to skin R20/21 Harmful by inhalation and in contact with skin
SAFETY PHRASES	S23 Do not breathe vapour/spray S24 Avoid contact with skin S38 In case of insufficient ventilation, wear suitable respiratory equipment S38/37 Wear suitable protective clothing and gloves S60 This material and container must be disposed of as hazardous waste
STATUTORY INSTRUMENTS	Chemicals (Hazard Information and Packaging) Regulations
APPROVED CODE OF PRACTICE	Classification and Labelling of Substances and Preparations Dangerous for Supply

16. OTHER INFORMATION

RISK PHRASES IN FULL	R10 Flammable
	R20/21 Harmful by inhalation and in contact with skin
	R20/21/22 Harmful by inhalation, in contact with skin and if swallowed
	R36 Irritating to eyes
	R36/38 Irritating to eyes and skin
	R37/38 Irritating to respiratory system and skin
	R38 Irritating to skin
	R41 Risk of serious damage to eyes
	R66 Repeated exposure may cause skin dryness or cracking
	R67 Vapours may cause drowsiness and dizziness